



Specification

Golf Cart Seating (Trimming)

Construction Properties		Standard	Remarks
Thickness		1.20mm	+/- 0.10mm
Width		54"	-0.5" / +1"
Weight		26 oz/yd ²	+/- 3 oz/yd ²
Backing		Polyester	Knock Stitched
Roll Size		40 yards	Standard
Formulation(1)		CPSIA Compliance	6P < 1,000PPM
Formulation(2)		Proposition 65	Lead content < 90PPM
Physical Properties		Standard	Remarks
Tensile Strength	MD	≥ 67 lbf	3 cm
	CD	≥ 67 lbf	
Elongation	MD	≥ 100%	3 cm
	CD	≥ 100%	
Tear Strength	MD	≥ 13 lbf	Trapezoid
	CD	≥ 6 lbf	
Adhesion Strength	MD	≥ 3 lbf	3 cm
	CD	≥ 3 lbf	
Abrasion		3,000 cycles, wire screen	CFFA-1a
Flex Resistance		25,000 cycles	CFFA-10
Croaking Resistance		Dry - No Stain	CFFA-7
Blocking Resistance		Class 2	CFFA-4
Cold Crack Resistance		ASTM D1790 Impact at -25°C	Pass
Fire Resistance		FMVSS302	Pass
Anti-UV Resistance		UVA-340nm at 600 hours	Pass
Mildew Resistance		ASTM G-21	Pass

Brochure disclaimer: All the test values are based on an average data in our lab and are believed to be true and accurate to the best of our knowledge.

This information does not constitute a warranty or guarantee, it will not relieve the user from the responsibility of the proper and safe use of the product.